

5% AXIAL LEADED RESISTOR

BRN BLK YEL GLD
1 0 4
 IN HOUSE P/N: 104
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

100k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED RED YEL GLD
2 2 4
 IN HOUSE P/N: 224
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

220k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

YEL VIO YEL GLD
4 7 4
 IN HOUSE P/N: 474
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

470k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN BRN YEL GLD
1 1 4
 IN HOUSE P/N: 114
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

110k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED YEL YEL GLD
2 4 4
 IN HOUSE P/N: 244
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

240k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

GRN BRN YEL GLD
5 1 4
 IN HOUSE P/N: 514
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

510k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN RED YEL GLD
1 2 4
 IN HOUSE P/N: 124
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

120k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED VIO YEL GLD
2 7 4
 IN HOUSE P/N: 274
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

270k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

GRN BLU YEL GLD
5 6 4
 IN HOUSE P/N: 564
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

560k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN ORN YEL GLD
1 3 4
 IN HOUSE P/N: 134
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

130k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN BLK YEL GLD
3 0 4
 IN HOUSE P/N: 304
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

300k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BLU RED YEL GLD
6 2 4
 IN HOUSE P/N: 624
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

620k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN GRN YEL GLD
1 5 4
 IN HOUSE P/N: 154
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

150k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN ORN YEL GLD
3 3 4
 IN HOUSE P/N: 334
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

330k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BLU GRY YEL GLD
6 8 4
 IN HOUSE P/N: 684
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

680k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN BLU YEL GLD
1 6 4
 IN HOUSE P/N: 164
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

160k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN BLU YEL GLD
3 6 4
 IN HOUSE P/N: 364
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

360k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

VIO GRN YEL GLD
7 5 4
 IN HOUSE P/N: 754
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

750k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN GRY YEL GLD
1 8 4
 IN HOUSE P/N: 184
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

180k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN WHT YEL GLD
3 9 4
 IN HOUSE P/N: 394
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

390k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

GRY RED YEL GLD
8 2 4
 IN HOUSE P/N: 824
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

820k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED BLK YEL GLD
2 0 4
 IN HOUSE P/N: 204
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

200k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

YEL ORN YEL GLD
4 3 4
 IN HOUSE P/N: 434
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

430k Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED BRN YEL GLD
9 1 4
 IN HOUSE P/N: 914
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

910k Ω

POWER 250mW